

© EPODOC / EPO

BEST AVAILABLE COPY

- PN - JP11175973 A 19990702
 TI - MASTER INFORMATION MAGNETIC RECORDER
 AB - PROBLEM TO BE SOLVED: To provide a master information magnetic recorder performing reliable pre-format recording by making a geometric center of a rugged shape **MARK** formed on a master information carrier precisely coincide with a rotational center of a magnetic recording medium.
 SOLUTION: A non-magnetic area 412 formed with no ferromagnetic layer is provided on a hard disk 41. A **MARK** 411 is provided on the master information carrier 42 matched with the position of the non-magnetic area 412 of the hard disk 41. The position of the master information carrier 42 is adjusted while observing an image obtained from a position detecting image pick-up device 410, and one side of the non-magnetic area 412 on the hard disk 41 is made to coincide with one side of the **MARK** 411 on the master information carrier 42, and both are stuck. Thereafter, a DC exciting magnetic field is applied to the master information carrier 42 by a permanent magnet 46, and a pre-format information signal answering to a rugged shape is recorded on the hard disk 41.
 FI - G11B5/86&101B
 PA - MATSUSHITA ELECTRIC IND CO LTD
 IN - MIYATA KEIZO; HAMADA TAZO; TOMA KIYOKAZU; RIYOUNAI HIROSHI; ISHIDA TATSURO
 AP - JP19970337363 19971208
 PR - JP19970337363 19971208
 DT - I


© WPI / DERWENT

- AN - 1999-435030 [37]
 TI - Master information magnetic recording device - **MARK** master information carrier and magnetic recording medium by matching position of non-magnetic area of recording medium to **MARK** provided in master information carrier
 AB - JP11175973 NOVELTY - The information signal corresponding to the uneven shape of the master information carrier is recorded to the magnetic recording medium. The master information carrier and magnetic recording medium are **aligned** by matching the position of the non-magnetic area of the recording medium to the **MARK** provided in the master information carrier. DETAILED DESCRIPTION - A ferromagnetic thin film is formed on the projection surface of an uneven-shaped master information carrier (42) formed on a base. A magnetic recording medium e.g. hard disc (41) is stuck to the film. Magnetization of the film is formed using an external magnetic field.
 - USE - For recording predetermined information signal beforehand to magnetic recording medium used in magnetic recording-and-reproducing apparatus of high capacity and high recording density e.g. hard disc drive.
 - ADVANTAGE - Pre-format recording without eccentricity can be performed since geometric center of uneven-shaped **MARK** formed on master information carrier can be made in accord with center of magnetic recording medium. DESCRIPTION OF DRAWING(S) - The figure shows a cross-sectional view of the master information recording device. (41) Hard disc; (42) Master information carrier.
 - (Dwg.4/17)
 IW - MASTER INFORMATION MAGNETIC RECORD DEVICE **ALIGN** MASTER INFORMATION CARRY MAGNETIC RECORD MEDIUM MATCH POSITION NON MAGNETIC AREA RECORD MEDIUM **MARK** MASTER INFORMATION CARRY
 PN - JP11175973 A 19990702 DW199937 G11B5/86 013pp
 IC - G11B5/86
 MC - T03-A07B
 DC - T03
 PA - (MATU) MATSUSHITA DENKI SANGYO KK
 AP - JP19970337363 19971208
 PR - JP19970337363 19971208

© PAJ / JPO

JP11175973


PN - JP11175973 A 19990702
TI - MASTER INFORMATION MAGNETIC RECORDER
AB - PROBLEM TO BE SOLVED: To provide a master information magnetic recorder performing reliable pre-format recording by making a geometric center of a rugged shape ~~411~~ formed on a master information carrier precisely coincide with a rotational center of a magnetic recording medium.
- SOLUTION: A non-magnetic area 412 formed with no ferromagnetic layer is provided on a hard disk 41. A ~~mark~~ 411 is provided on the master information carrier 42 matched with the position of the non-magnetic area 412 of the hard disk 41. The position of the master information carrier 42 is adjusted while observing an image obtained from a position detecting image pick-up device 410, and one side of the non-magnetic area 412 on the hard disk 41 is made to coincide with one side of the ~~mark~~ 411 on the master information carrier 42, and both are stuck. Thereafter, a DC exciting magnetic field is applied to the master information carrier 42 by a permanent magnet 48, and a pre-format information signal answering to a rugged shape is recorded on the hard disk 41.
I - G11B6/86
PA - MATSUSHITA ELECTRIC IND CO LTD
IN - MIYATA KEIZO;HAMADA TAIZO;TOMA KIYOKAZU;RIYOUNAI HIROSHI;ISHIDA TATSURO
ABD - 19991029
ABV - 199912
AP - JP19970337363 19971208




(12)

特開平11-175973


【図7】




【図8】




【図11】




【図9】




【図17】



【図12】




【図13】




(11)

特開平11-175973


【図1】




【図2】




【図4】



【図6】



【図10】



**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☐ FADED TEXT OR DRAWING
- ☐ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☒ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☒ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☒ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.